

LineLED PRO INOX

Moisture-proof diffuser lights



LineLED PRO INOX

The LineLED PRO INOX is the V2A stainless steel light for demanding applications in industrial plants, underground garages as well as cooling and storage areas. The stainless steel casing is virtually indestructible and durable.

An impact-resistant and satin-finished polycarbonate (PC) cover minimises glare and ensures a uniform light distribution with a high visual comfort. The high protection class IP65 prevents dirt and water from entering the light. All versions are standard-designed for 5x2.5sqmm feed-through wiring. The cable bushing is suitable for supply lines with an outside diameter of 5 to 12 mm.

Product properties

- robust stainless steel casing
- closures and fastenings made of stainless steel
- full luminous flux, available immediately
- low energy consumption with high luminous efficacy
- shockproof cover (IK08)
- high energy efficiency
- no maintenance
- no UV/IR radiation
- incl. feed-through wiring 5x2.5sqmm

Technical data

Input voltage	220-240VAC
Light source	LED
System output	50W / 62W
Luminous flux	6250lm / 8125lm
System efficiency	125 lm/W
Light colour	5000K
CRI Index	Ra >80
Beam angle	90°
LED service life	50000h [L70/B30]
Protection type	IP65
Protection class	I
Impact resistance	IK08
Temperature application range	-20°C to +40°C
Casing material	V2A
Cover	PC matt
Weight	approx 3.7kg / 4.5kg
Dimensions (LxWxH)	1300x67x115mm 1600x67x115mm

Assortment

Item no.	Description
294015	LineLED-PRO INOX/W50V230/1300mm/DV5X2,5/-
294016	LineLED-PRO INOX/W62V230/1600mm/DV5X2,5/-