



## READY FOR THE TOUGHEST MISSIONS.

Tested safety for your protection: With our mobile solid rubber distributors you can rely on a trouble-free experience at changing locations. GIFAS stands for proven quality when it comes to materials and components, ensuring that things run smoothly on site.

Small distributors	44
Adapters	45
Industrial distributors	46
Distributor on hinged stand	50
Moveable distributors	51
Inspection trolleys	52
Application cases	53

# Small distributors

## Series 1400 / 1800 / 2000

Item no.	Symbols Output	Output	Input	Cable/personal protection
----------	----------------	--------	-------	---------------------------

### Series 1400 / 78x290x91mm Weight 2-2,5kg Protection category IP54

Assembly variants



Item no. 210521



210502		2 protective contact 230V	3m 3x1.5mm <sup>2</sup> Protective contact	RCCB 25/0.03A 2p.
246104		2 protective contact 230V	3m 3x1.5mm <sup>2</sup> CEE 3x16A/230V	RCCB 25/0.03A 2p.
210521		4 protective contact 230V	3m 3x1.5mm <sup>2</sup> Protective contact	
241761		4 protective contact 230V	5m 3x1.5mm <sup>2</sup> Protective contact	

can be supplied with transparent protective cap for max. 2 automated units

### Series 1800 / 92x184x53mm Weight 2kg Protection category IP54

Assembly variants



Item no. 101294



101291		3 protective contact 230V	Anti-kink sleeve 3x1.5mm <sup>2</sup>	
101294		3 protective contact 230V	3m 3x1.5mm <sup>2</sup> Protective contact	
101296		3 protective contact 230V	5m 3x1.5mm <sup>2</sup> Protective contact	
101297		3 protective contact 230V	10m 3x1.5mm <sup>2</sup> Protective contact	
200804		3 protective contact 230V	3m 5x2.5mm <sup>2</sup> CEE 5x16A/400V	

### Series 2000 / 130x115x130mm Weight 2-3kg Protection category IP54

Assembly variants



Item no. 101329



101329		3 protective contact 230V	3m 5x2.5mm <sup>2</sup> CEE 5x16A/400V	
101337		1 CEE 5x16A/400V 2 protective contact 230V	3m 5x2.5mm <sup>2</sup> CEE 5x16A/400 V	
101344		3 CEE 2x16A/24V	3m 2x2.5mm <sup>2</sup> CEE 2x16A/24V	
101353		3 CEE 2x16A/42V	3m 2x2.5mm <sup>2</sup> CEE 2x16A/42V	
114899		3 CEE 4x16A/>50V, 10h high-frequency 100-300Hz	3m 4x2.5mm <sup>2</sup> CEE 4x16A/>50V, 10h high-frequency 100-300Hz	

with 4 adjustable feet and carrying handle


Tailored, customised equipment according to choice.

**Series 2516**

Item no.	Symbols Output	Output	Input	Cable/personal protection
----------	----------------	--------	-------	---------------------------

Series 2516 / 250x160x90mm Weight ca. 2-4kg Protection category IP54

Assembly variants




209807		4 protective contact 230V	3m 3x1.5mm <sup>2</sup> Protective contact	RCCB 25/0.03A 2p.
301255		4 protective contact 230V	5m 3x1.5mm <sup>2</sup> Protective contact	PRCD-S+ 16/0,03A
210397		6 protective contact 230V	3m 5x2.5mm <sup>2</sup> CEE 5x16A/400V	
237840		1 CEE 5x16A/400V	3m 5x2.5mm <sup>2</sup> CEE 5x16A/400V	RCCB 25/0.03A 4p.
237843		1 CEE 5x32A/400V	3m 5x6mm <sup>2</sup> CEE 5x32A/400V	RCCB 40/0.03A 4p.
247671		3 CEE 2x16A/24V	1 KV M20 from below	

Distributors equipped with solid rubber-carrying handle

Series 3020 / 300x200x110mm Weight 4kg Protection category IP54

Assembly variants



289380		3 protective contact 230V 1 protective contact 230V red	1 CEE 5x16A/400V Built-in appliance plug 1 Main switch 20A 1 Three-phase electricity meter 40A	LS 16A.1PC LS 16A.1PC FI 25/0,03A 4p.
--------	--	--	---	---

**Adapters**

**Notes**

- The setup requirements for adapters are subject to the conditions of VDE series 0623 - especially part 4 - or in approximation to these.
- An adapter always comprises three parts and is made up of a plug, connecting cable and socket part (e.g. connector socket).
- The flexible connecting cable must be at least 1 m long in order to relieve strain on the wall-mounted socket.
- Not permitted are single-part adapters in which the plug and socket part of both systems are mechanically built together and operated from a single socket since the sockets are not designed for the resulting mechanical rigidity in the event of horizontal and vertical tensile stresses (lever effect).
- Adapters are only intended for short-term use, therefore a clearly visible external warning >For time-limited use only< is required.

Item no.	Output	Input	Cable / personal protection
251882	1 protective contact 230V	2m 5x2.5mm <sup>2</sup> CEE plug 5x16A/400V	1 MCB 16A.1PB
251883	1 protective contact 230V	2m 5x6,0mm <sup>2</sup> CEE plug 5x32A/400V	1 MCB 16A.1PB
251885	1 CEE 5x16A/400V	2m 5x6,0mm <sup>2</sup> CEE plug 5x32A/400V	1 MCB 16A.3PC
251935	1 CEE 5x16A/400V	2m 5x16.0mm <sup>2</sup> CEE plug 5x63A/400V	1 MCB 16A.3PC
251886	1 CEE 5x32A/400V	2m 5x16.0mm <sup>2</sup> CEE plug 5x63A/400V	1 MCB 32A.3PC



Item no. 209807



Item no. 301255



Item no. 289380



Item no. 251883 and 251882



Item no. 251885



Item no. 251935 and 251886



## Series 1812 / 2516 / 6200 / 6700 Meter with MID approval inside

Item no.	Symbols Output	Output	Input	Cable/personal protection
----------	----------------	--------	-------	---------------------------

### Series 1812 / 125x180x90mm Weight ca. 2kg Protection category IP54

Assembly variants




Item no. 295153

295153		1 protective contact 230V	3m 3x1,5mm <sup>2</sup> protective contact 1 digital AC meter 40A*	
296878		1 protective contact 230V	3m 3x1,5mm <sup>2</sup> protective contact 1 AC meter 32A with roller counter*	
296161		2 protective contact 230V	3m 3x1,5mm <sup>2</sup> protective contact 1 digital AC meter 40A*	
296723		2 protective contact 230V	3m 3x1,5mm <sup>2</sup> protective contact 1 AC meter 32A with roller counter*	

### Series 2516 / 160x250x90mm Weight ca. 3kg Protection category IP54

Assembly variants




Item no. 294916

294802		3 protective contact 230V	3m 3x1,5mm <sup>2</sup> protective contact 1 digital AC meter 40A*	
294916		1 CEE 5x16A/400V	3m 5x2,5mm <sup>2</sup> CEE 5x16A/400V 1 digital three-phase current meter 40A*	
294804		1 CEE 5x16A/400V 2 protective contact 230V	3m 5x2,5mm <sup>2</sup> CEE 5x16A/400V 1 digital three-phase current meter 40A*	
295381		1 CEE 5x32A/400V	3m 5x6mm <sup>2</sup> CEE 5x32A/400V 1 digital three-phase current meter 40A*	

### Series 6200 / 275x280x230mm Weight ca. 7kg Protection category IP54

Assembly variants




Item no. 253659

250654		1 CEE 5x32A/400V	3m 5x6mm <sup>2</sup> CEE 5x32A/400V 1 digital three-phase current meter 40A*	
253659		1 CEE 5x63A/400V	3m 5x16mm <sup>2</sup> CEE 5x63A/400V 1 digital three-phase current meter 65A*	

### Series 6700 / 305x350x280mm Weight ca. 14kg Protection category IP54

Assembly variants



Item no. 295327

271044		1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	3m 5x6mm <sup>2</sup> CEE 5x32A/400V 1 digitaler Drehstromzähler 40A*	1 LS 16A.3PC 3 LS 16A.1PB 1 FI 40/0,03A 4p.
295327		2 CEE 5x32A/400V 4 protective contact 230V	3m 5x6mm <sup>2</sup> CEE 5x32A/400V 1 digitaler Drehstromzähler 40A*	4 Neozed 16A 1 FI 40/0,03A 4p.
293745		1 CEE 5x125A/400V	3m 5x25mm <sup>2</sup> CEE 5x125A/400V 1 digitaler Drehstromzähler 125A*	

\* AC meters with MID approval, electricity meters also all available with roller counter.


Tailored, customised equipment according to choice.

**Series 3800 PRCD-S inside / 6200**

Item no.	Symbols Output	Output	Input	Cable/personal protection
----------	----------------	--------	-------	---------------------------

**Series 3800 PRCD-S inside / 250x360x132mm Weight 5-8kg Protection category IP54**

Assembly variants




291353		1 CEE 5x16A/400V	3m 5x2,5mm <sup>2</sup> CEE 5x16A/400V	PRCD-S 400V/16A
291351		1 CEE 5x32A/400V	3m 5x6mm <sup>2</sup> CEE 5x32A/400V	PRCD-S 400V/32A



Illustration similar

**Series 6200 / 280x275x230mm Weight ca. 6-8kg Protection category IP54**

Assembly variants



208405		6 protective contact 230V	CEE 5x16A/400V device connector	RCCB 25/0.03A 4p.
208981		1 CEE 5x16A/400V 3 protective contact 230V	3m 5x2.5mm <sup>2</sup> CEE 5x16A/400V	RCCB 25/0.03A 4p.
207754		1 CEE 5x16A/400V 3 protective contact 230V	3m 5x2.5mm <sup>2</sup> CEE 5x16A/400V	
209315		1 CEE 5x16A/400V 3 protective contact 230V	CEE 5x16A/400V connector plug	
208979		1 CEE 5x16A/400V 3 protective contact 230V	3m 5x6,0mm <sup>2</sup> CEE 5x32A/400V	Neozed 16A Neozed 16A
207755		1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	3m 5x6,0mm <sup>2</sup> CEE 5x32A/400V	Neozed 16A Neozed 16A

- can also be supplied with circuit breaker switch
- with max. 9 automated units inside located under the cover plate

**TOP !**



Item no. 207755

**TOP !**



Automated units under cover plate

Tailored, customised equipment according to choice.

# Industrial distributors

## Series 6700 / 7900

Item no.	Symbols Output	Output	Input	Cable/personal protection
----------	----------------	--------	-------	---------------------------

### Series 6700 / 350x305x280mm Weight ca. 12-14kg Protection category IP54

Assembly variants



TOP !

TOP !



Item no. 209311



Item no. 240184 with Marechal-sockets

209311		1 CEE 5x32A/400V 1 CEE 5x16A/400V 2 protective contact 230V	3m 5x6,0mm <sup>2</sup> CEE 5x32A/400V	MCB 16A.3PC MCB 16A.1PB RCCB 40/0.03A 4p.
208959		1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	3m 5x6,0mm <sup>2</sup> CEE 5x32A/400V	Neozed 16A Neozed 16A RCCB 40/0.03A 4p.
209307		1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	3m 5x16,0mm <sup>2</sup> CEE 5x63A/400V	MCB 32A.3PC MCB 16A.3PC MCB 16A.1PB
208960		1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	3m 5x16,0mm <sup>2</sup> CEE 5x63A/400V	Neozed 25A Neozed 16A Neozed 16A RCCB 63/0.03A 4p.
209516		1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	CEE 5x63A/400V device connector	Neozed 25A Neozed 16A Neozed 16A RCCB 63/0.03A 4p.
209167		1 CEE 5x32A/400V 2 CEE 5x16A/400V 3 protective contact 230V	3m 5x6,0mm <sup>2</sup> mit CEE 5x32A/400V	Neozed 16A Neozed 16A
209515		1 CEE 5x32A/400V 2 CEE 5x16A/400V 3 protective contact 230V	CEE 5x32A/400V device connector	Neozed 16A Neozed 16A
209517		1 CEE 5x63A/400V 1 CEE 5x32A/400V 1 CEE 5x16A/400V 3 protective contact 230V	CEE 5x63A/400V device connector	MCB 32A.3PC MCB 16A.3PC MCB 16A.1PB RCCB 63/0.03A 4p.
240184		1 Marechal-sockets 5x90-150A/500V	1 bellmouth cable gland M 50	RCCB 125/0.03A 4p.




Item no. 231829

### Series 7900 / 360x500x173mm Weight 23kg Protection category IP54

with main switch

Assembly variants



231829		12 protective contact 230V	3m 5x6,0mm <sup>2</sup> CEE 5x32A/400V	MCB 16A.1PC RCCB 40/0.03A 4p. for 6 protective contact each
--------	--	----------------------------	---	--


Tailored, customised equipment according to choice.

**Series 7900**

Item no.	Symbols Output	Output	Input	Cable/personal protection
----------	----------------	--------	-------	---------------------------

**Series 7900 / 360x500x173mm Weight 23kg Protection category IP54**

Assembly variants



209257		2 CEE 5x16A/400V 6 protective contact 230V	CEE 5x32A/400V device connector	Neozed 16A MCB 16A.1PB RCCB 40/0.03A 4p. RCCB 40/0.03A 4p.
210631		1 CEE 5x32A/400V 2 CEE 5x16A/400V 9 protective contact sockets 230V	3m 5x6.0mm <sup>2</sup> CEE 5x32A/400V	Neozed 25A Neozed 16A Neozed 16A RCCB 40/0.03A 4p. f.6 protective contacts RCCB 40/0.03A 4p. f. remaining sockets
230776		1 CEE 5x32A/400V 4 CEE 5x16A/400V 3 protective contact sockets 230V	3m 5x16.0mm <sup>2</sup> CEE 5x63A/400V	Neozed 25A Neozed 16A Neozed 16A RCCB 63/0.03A 4p. for CEE RCCB 25/0.03A 4p. for protective contact
210884		2 CEE 5x32A/400V 6 protective contact 230V	3m 5x16.0mm <sup>2</sup> CEE 5x63A/400V	Neozed 25A MCB 16A.1PB RCCB 63/0.03A 4p. RCCB 40/0.03A 4p.
233393		2 CEE 5x32A/400V 4 CEE 5x16A/400V 3 protective contact sockets 230V	3m 5x16.0mm <sup>2</sup> CEE 5x63A/400V	MCB 32A.3PC MCB 16A.3PC MCB 16A.1PB RCCB 63/0.03A 4p. for CEE 32A and protective contact RCCB 63/0.03A 4p. for CEE 16A
210630		1 CEE 5x32A/400V 2 CEE 5x16A/400V 10 protective contact 230V	3m 5x6.0mm <sup>2</sup> CEE 5x32A/400V	Neozed 25A Neozed 16A Neozed 16A RCCB 40/0.03A 4p.
204298		1 CEE 5x63A/400V 2 CEE 5x32A/400V 2 CEE 5x16A/400V 3 protective contact 230V	3m 5x16.0mm <sup>2</sup> CEE 5x63A/400V	Neozed 63A Neozed 25A Neozed 16A Neozed 16A RCCB 63/0.03A 4p.
211029		2 CEE 5x63A/400V 2 CEE 5x32A/400V 3 protective contact 230V	CEE 5x125A/400V device connector	Neozed 63A Neozed 25A Neozed 16A RCCB 125/0.03A 4p.
287699		1 CEE 5x32A/400V 1 CEE 5x16A/400V 9 Schuko 230V 1 Schuko 230V rot	1 CEE 5x63A/400V Built-in appliance plug 1 Main switch 63A 1 Three-phase electricity meter 63A	MCB 32A.3PC MCB 16A.3PC MCB 16A.1PC MCB 16A.1PC RCCB 63/0.03A 4p.
277359		12 protective contact sockets 230V	CEE 5x32A/400V device connector	12 MCB 16A.1PC 12 RCCB 40/0.03A 4p. for 6 protective contact

**TOP!**



7900 engraving according to customers requirements



Item no. 287699

- with max. 51 automated units (17 per transparent protective cap), with 4 adjustable feet and 1 or 2 carrying handles
- Distributor equipped with transport handle and leveling feet

Tailored, customised equipment according to choice.

## Distributor on hinged stand



7300 on hinged stand



7400 on hinged stand



7700 on hinged stand

For complex applications (e.g. larger temporary construction sites) wall-mounted distribution boxes with handles are available as an alternative to the classic design of mobile distribution boxes. These can be mounted on a hinged frame. Flexible, versatile assembly options allow the appropriate power supply on site. Thanks to the universal hinged frame, series 7200 to 7700 distribution boxes can be used.

### Product features hinged stand

- Mobile solution for larger distributors with a wide range of equipment options
- Practical carry case
- Mounting holes for different series
- Solid stainless steel version in V2A
- Protective devices can be viewed and operated directly via the transparent protection flap
- Better operability due to elevated position
- Protection against waterlogging

### Technical data

Material	V2A stainless steel I
Dimensions (HxWxD)	569x400x40mm

Item no.	Description
294668	Hinged stand for distributors of the series 7200 - 7700



Optional:  
Stand MINI with double feet



## Moveable distributors

Item no.	Symbols Output	Output	Input	Cable/personal protection
<b>Distributor 7900 / 360x500x173mm Protection category IP54</b> <b>Zinc-plated chassis / 450x977x447mm Weight ca. 55kg</b>				
209455		1 CEE 5x63A/400V 1 CEE 5x32A/400V 2 CEE 5x16A/400V 6 protective contact sockets 230V	3m 5x16mm <sup>2</sup> CEE 5x63A/400V	Neozed 32A Neozed 16A 6 MCB 16A.1PB RCCB 63/0.03A 4p. for all CEE RCCB 40/0.03A 4p. for all protective contacts, IP54
279096		1 CEE 5x63A/400V 1 CEE 5x32A/400V 2 CEE 5x16A/400V 6 protective contact sockets 230V	3m 5x16mm <sup>2</sup> CEE 5x63A/400V	Neozed 32A Neozed 16A 6 MCB 16A.1PB RCCB 63/0.03A 4p. for all CEE RCCB 40/0.03A 4p. for all protective contacts, IP67



Item no. 209455

Item no. 279096

**Distributor 7400 / 265x370x132mm Protection category IP54**  
**Hand truck / 566x1200x560mm Weight ca. 81kg**

233431		1 CEE 5x32A/400V 1 CEE 5x16A/400V 2 protective contact 230V	40m 5x6mm <sup>2</sup> CEE 5x32A/400V	1 MCB 16A.3PC 2 MCB 16A.1PB RCCB 40/0.03A 4p.
--------	--	---	--	---



Item no. 233431

Item no. 295316

**Distributor 7900 / 2x 360x500x173mm Protection category IP54**  
**Barrow / 566x1250x560mm Weight ca. 65kg**

295316		1 CEE 5x63A/400V 2 CEE 5x32A/400V 2 CEE 5x16A/400V 6 protective contact 230V	5m 5x35mm <sup>2</sup> CEE 5x32A/400V 1 energy meter 1 Kunbus Revolution Pi 1 control fuse 2A 1 power supply unit 24 V 1 glass tube fuse 1A 1 RJ45 data socket	1 MCP 63A.3PC 2 MCP 32A.3PC 2 MCP 16A.3PC 6 MCP 16A.1PB 2 RCCB 63/0,03A 4p. Typ B 1 RCCB 40/0,03A 4p. Typ B 1 RCCB 40/0,03A 4p.
--------	--	---	---	---

**Distributor 7800 / 360x500x133mm Protection category IP54**  
**Sheet steel cable reel red 521 movable / 720x1130x775mm Weight ca. 90kg**

207356		2 CEE 5x32A/400V 2 CEE 5x16A/400V 3 protective contact 230V	25m 5x16mm <sup>2</sup> CEE 5x63A/400V	Neozed 32A Neozed 16A 3 MCB 16A.1PB RCCB 25/0.03A 4p.
--------	--	---	---	--



Item no. 207356

Tailored, customised equipment according to choice.

## Inspection trolley / Mobil electronic frequency converter / Test unit

These products are equipped entirely in accordance with your wishes and requirements. Our experience and your needs are perfectly tuned to produce the ideal solution. The possibilities are virtually limitless.

### Possible areas of use

aircraft construction, automotive industry, tool manufacturing, major inspections, assembly, large-scale construction sites, testing and assembly stations in industry, concerts and festivals, theatre stages

### Installation possibilities

transformers (three-phase current, safety or isolating transformers), control elements, measuring equipment, fuse elements, control lights, insulation monitors, plug connectors, and much more



Test unit



Inspection trolley



Inspection trolley



Mobile frequency converter



Inspection trolley „3 in 1“ - transformer, big cable reel, trailer, rotary current transformer

Tailored, customised equipment according to choice.

Application cases mobile distributor



# WE ARE EXPERTS IN YOUR FIELD


## Mobile distributors



Construction industry



Industrial sector



Safety equipment

**THE GIFAS WORLD.**

**All products for your sector at a glance.**

**More on [www.gifas.de/en/gifas-world](http://www.gifas.de/en/gifas-world)**